QUICKLIFT USA

QL12KBP

TWO POST BASEPLATE LIFT

12,000LB BASEPLATE



12,000 LB LIFTING CAPACITY
LOW-CEILING BASEPLATE DESIGN | NO OVERHEAD BEAM
73.25" MAXIMUM LIFT HEIGHT | 82.25" WITH ADAPTERS
TWO WIDTH SETTINGS | 118.25" OR 123.5" BETWEEN COLUMNS
2 HP | 220V SINGLE-PHASE ELECTRIC/HYDRAULIC SYSTEM
FOUR SYMMETRICAL THREE-STAGE ARMS
AUTOMATIC ARM RESTRAINTS | SINGLE-POINT SAFETY RELEASE
DUAL HYDRAULIC CYLINDERS | CHAIN DRIVE | EQUALIZER CABLES
REINFORCED COLUMN BASES | PROTECTIVE FLOOR COVER
INCLUDES 3" & 6" EXTENSION ADAPTERS | ADJUSTABLE SCREW PADS
MINIMUM CONCRETE | 6" THICK | 3,500 PSI
AUTOMATIC TWO-YEAR WARRANTY ON ALL NON-WEARABLE PARTS

CAPACITY	MAX LIFTING HEIGHT	OVERALL HEIGHT	OVERALL WIDTH	DRIVE-THRU CLEARANCE	WIDTH BETWEEN COLUMNS	MIN. PAD HEIGHT	GROSS WEIGHT	MOTOR
12,000LB	73.25"	122.5"	145.5" / 150.75"	104.5" / 110"	118.25" / 123.5"	4.75"	2,150LB	2 HP / 220V

3380 S POWER RD #105,
GILBERT, AZ 85234

WWW.QUICKLIFTUSA.COM
602-828-0950

SALES | SERVICE | INSTALL