QUICKLIFT USA

QL15KCF

TWO POST CLEAR FLOOR LIFT

15,000LB CLEAR FLOOR



15,000 LB LIFTING CAPACITY
75"-76.25" MAXIMUM LIFT HEIGHT | ADJUSTABLE SCREW PADS
109.75" DRIVE-THROUGH CLEARANCE
CLEAR FLOOR DESIGN FOR AN UNRESTRICTED WORKSPACE
2 HP | 220V SINGLE-PHASE ELECTRIC/HYDRAULIC SYSTEM
FOUR HEAVY-DUTY SYMMETRICAL TWO-STAGE ARMS
SINGLE-POINT SAFETY RELEASE AND OVERHEAD SHUT-OFF DEVICE
INCLUDES 3" AND 6" EXTENSION ADAPTERS | ADJUSTABLE SCREW PADS
SELF-LUBRICATING UHMW POLYETHYLENE SLIDERS AND BRON E BUSHINGS
HD SADDLE ADAPTERS INCLUDED AS STANDARD EQUIPMENT
MINIMUM CONCRETE REQUIREMENT | 6" THICK | 3,500 PSI

CAPACITY	MAXIMUM LIFTING HEIGHT	OVERALL HEIGHT	OVERALL WIDTH	DRIVE-THROUGH CLEARANCE	WIDTH BETWEEN COLUMNS	MIN. PAD HEIGHT	GROSS WEIGHT	MOTOR
15,000 lb	75"-76.25"	174 / 186 / 198"	150.75"	109.75"	123.5"	7"	2,573 lb	2 HP / 220V

3380 S POWER RD #105,
GILBERT, AZ 85234

WWW.QUICKLIFTUSA.COM
602-828-0950

SALES | SERVICE | INSTALL