QUICKLIFT USA

THREE-PHASE AIR COMPRESSOR



QL-20HP



QL-30HP



QL-40HP



QL-50HP

20 / 30 / 40 / 50 HP | THREE-PHASE

PRODUCT DESCRIPTION

- 20 HP / 30 HP / 40 HP / 50 HP
- THREE-PHASE POWER
- 220 V / 60 Hz power
- Variable-speed, direct-drive design
- 145 PSI maximum operating pressure
- Oil-injected rotary screw airend
- Continuous-duty operation
- Digital status and alarm display
- External air receiver required
- Scheduled service packages available
- 3-year manufacturer warranty
- Free local delivery within 25 miles

Technical Parameters

SPECIFICATION	QL-20HP	QL-30HP	QL-40HP	QL-50HP
MOTOR POWER	20 HP	30 HP	40 HP	50 HP
MAX. PRESSURE	145 PSI	145 PSI	145 PSI	145 PSI
RATED AIRFLOW, CFM	31.32-78.3	45.9-114.77	63.56-158.91	79.18-197.76
SUPPLY	220 V / 60 Hz	220 V / 60 Hz	220 V / 60 Hz	220 V / 60 Hz
PHASE	3	3	3	3
LENGTH, in.	43.90	52.56	60.23	60.10
WIDTH, in.	29.75	35.82	41.73	41.48
HEIGHT, in.	43.15	43.30	50.78	50.69
DRY WEIGHT, lb	859.8	1036.17	1322.77	1587.33
SOUND, dB(A)	62 +/- 2	64 +/- 2	66 +/- 2	66 +/- 2
AIR OUTLET	G3/4	G1	G1-1/2	G1-1/2
DRIVE	DIRECT	DIRECT	DIRECT	DIRECT
RECEIVER	EXTERNAL	EXTERNAL	EXTERNAL	EXTERNAL

Quick Lift USA three-phase rotary screw compressors are available in 20 HP, 30 HP, 40 HP and 50 HP sizes. Each standalone unit combines variable-speed direct drive, an oil-injected airend, an enclosed cabinet and digital controls. All operate on 220 V / 60 Hz three-phase power.

Connect to a properly sized external ASME-certified receiver, dryer and filters as required. Service packages available. Free local delivery within 25 miles of Gilbert, AZ; nationwide shipping available.

THREE-PHASE SINGLE UNITS







ACCREDITED BUSINESS
BBB

QUICKLIFT USA

OPEN TO THE PUBLIC
3380 SOUTH POWER ROAD #105
GILBERT, AZ 85234

CALL/TEXT
602-828-0950
INFO@QUICKLIFTUSA.COM