QUICKLIFT USA

QL6KRBG

AIR JACKING BEAM

6,000 LB CAPACITY



FOR QUICK LIFT 10K & HD 12K FOUR-POST LIFTS
AIR-OVER-HYDRAULIC FOOT PUMP
WHEEL, BRAKE & SUSPENSION SERVICE
ROLLING DESIGN | ADJUSTABLE ARMS & SUPPORT BASE
RUBBER PADS | TWO 2.5 IN. EXTENSION ADAPTERS
MECHANICAL SAFETY LOCK
GREATER THAN 116 PSI AIR SUPPLY REQUIRED
AIR FILTER / WATER SEPARATOR REQUIRED
AIR COMPRESSOR NOT INCLUDED
2-YEAR MANUFACTURER WARRANTY

CAPACITY	PAD REACH	SUPPORT-BASE SPAN	MIN. PAD HEIGHT	MAX. HEIGHT WITH ADAPTERS	MODEL
6,000 lb	33.07-53.43 in.	33.86-52.83 in.	8.62 in.	20.28 in.	QL6KRBG

Rounded dimensions; see manual for exact measurements.

3380 S POWER RD #105,
GILBERT, AZ 85234

WWW.QUICKLIFTUSA.COM
602-828-0950

SALES | SERVICE | INSTALL