QUICKLIFT USA

# REFRIGERATED AIR DRYERS




QLAD57




QLAD1020

5-7.5 HP / 10-20 HP COMPRESSOR RANGES

## PRODUCT DESCRIPTION

- Two compressor-size ranges
- 220 V / single-phase / 50 Hz
- Aluminum plate-fin heat exchanger
- Automatic condensate drainage
- Indoor, air-cooled design
- 35.6-50°F pressure dew point
- Local controls and fault indication
- G1 (1 in. BSPP) air connections
- Compact cabinet with service access
- 2-year manufacturer warranty
- Free local delivery within 25 miles
- Nationwide shipping available

## Technical Parameters

| SPECIFICATION | QLAD57 | QLAD1020 |
|---|---|---|
| COMPRESSOR RANGE | 5-7.5 HP | 10-20 HP |
| RATED AIRFLOW, CFM | 60.32 | 91.82 |
| RATED INLET PRESSURE | 101.5 PSI | 101.5 PSI |
| MAX. INLET PRESSURE | 232 PSI | 232 PSI |
| MAX. INLET AIR TEMP. | 140°F | 140°F |
| PRESSURE DEW POINT | 35.6-50°F | 35.6-50°F |
| POWER SUPPLY | 220 V / 1 PH / 50 Hz | 220 V / 1 PH / 50 Hz |
| AIR CONNECTIONS | G1 / 1 in. BSPP | G1 / 1 in. BSPP |
| LENGTH, in. | 20.87 | 20.87 |
| WIDTH, in. | 17.72 | 18.11 |
| HEIGHT, in. | 27.91 | 29.80 |
| WEIGHT, lb | 99.21 | 110.23 |
| REFRIGERANT | R134a | R410A |

Quick Lift USA refrigerated air dryers cool compressed air to condense and separate moisture, then discharge collected water through an automatic drain. Choose QLAD57 for the 5-7.5 HP range or QLAD1020 for the 10-20 HP range, sized to actual airflow and conditions.

Rated flow: 101.5 PSI inlet pressure and 113°F inlet air. Indoor ambient: 33.8-100.4°F. 2-year manufacturer warranty. Free local delivery within 25 miles of Gilbert, AZ; nationwide shipping available.

REFRIGERATION & HEAT-EXCHANGER COMPONENTS







ACCREDITED BUSINESS

QUICKLIFT USA

OPEN TO THE PUBLIC
3380 SOUTH POWER ROAD #105
GILBERT, AZ 85234

CALL/TEXT
602-828-0950
INFO@QUICKLIFTUSA.COM