QUICKLIFT USA

QL9KBP

TWO POST BASEPLATE LIFT

9,000LB BASEPLATE



9,000 lb Lifting Capacity

Low-Ceiling Baseplate Design | No Overhead Beam

76.5"–78.25" Maximum Lifting Height | Adjustable Screw Pads

100.75" Drive-Through Clearance

110V Single-Phase | Prewired Grounded Three-Prong Plug

Durable Gray-and-Black Powder-Coat Finish

Automatic Arm Restraints | Single-Point Safety Release

Includes 3" Extension Adapters and Adjustable Screw Pads

Dual Hydraulic Cylinders | Chain Drive | Equalizer Cables

Four Symmetrical Three-Stage Arms

Automatic Two-Year Warranty on All Non-Wearable Parts

CAPACITY	MAX. LIFTING HEIGHT	OVERALL HEIGHT	OVERALL WIDTH	DRIVE-THROUGH CLEARANCE	WIDTH BETWEEN COLUMNS	MIN. PAD HEIGHT	GROSS WEIGHT	POWER SUPPLY
9,000 lb	76.5"–78.25"	112"	136.25"	100.75"	112.25"	3.5"	1,581 lb	110V

Rounded dimensions. Lift height varies with pad adjustment; see manual for exact ranges.

3380 S POWER RD #105,
GILBERT, AZ 85234

WWW.QUICKLIFTUSA.COM
602-828-0950

SALES | SERVICE | INSTALL